

Description

Fastener Length: 3-1/2", Thread: 3/8-24, Head Width: 5/16", Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000645
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-206-5811
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20006-45 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Fastener Length:	3.485 Inches Minimum And 3.515 Inches Maximum
Head Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Head Height:	0.375 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.