

## P/N MS20006H16

### **Description**

Fastener Length: 1-11/16", Hole Diameter: 1/16", Thread: 3/8-24, Head Width: 5/16", Thread Length: 43/64

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS20006H16
Minimum Qty (MOQ):	2
NSN:	5306-00-584-5156
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20006H16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.663 Inches Minimum And 0.713 Inches Maximum
Fastener Length:	1.673 Inches Minimum And 1.703 Inches Maximum
Head Style:	Bevel-conical Service Control of the
Head Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Head Height:	0.365 Inches Minimum And 0.385 Inches Maximum
Hole Diameter:	0.055 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this internal wrenching bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006H16">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006H16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006H16">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006H16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006H16">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006H16</a> and selecting the