

Description

MS20007-12 Internal Wrenching Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS2000712 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-00-297-4260 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE
AVAILABLE

P/N MS20007-12 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.812 Inches Minimum |
| Fastener Length: | 1.562 Inches Nominal |
| Head Diameter: | 0.740 Inches Minimum And 0.750 Inches Maximum |
| Head Height: | 0.438 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.438 Inches |
| Width Across Flats: | 0.313 Inches Minimum And 0.315 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Nominal Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20007-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.