

## P/N MS20007-26

### **Description**

Fastener Length: 2-7/16", Thread: 7/16-20, Head Width: 5/16", Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS2000726
Minimum Qty (MOQ):	1
NSN:	5306-00-639-2968
Schedule B:	7318.15.8085
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20007-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.812 Inches Nominal
Fastener Length:	2.438 Inches Nominal
Head Style:	Bevel-conical
Head Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.438 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.438 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

## **How to Order**

Order this internal wrenching bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20007-26">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20007-26</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.