

P/N MS20007-36

Description

length: 3-1/16", grip: 2-1/4", thread: 7/16-20, internal wrenching, cadmium plated alloy steel, MS20007 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2000736

Minimum Qty (MOQ):

NSN: 5306-00-638-3161

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N MS20007-36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.812 Inches Minimum
Fastener Length:	3.047 Inches Minimum And 3.077 Inches Maximum
Head Style:	Bevel-conical Seven Seve
Head Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.438 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.438 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20007-36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.