

**Description**

length: 3-7/16", grip: 2-5/8", thread: 7/16-20, internal wrenching bolt, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2000742
Minimum Qty (MOQ):	1
NSN:	5306-00-638-3176
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS20007-42 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.812 Inches Minimum
<b>Fastener Length:</b>	3.423 Inches Minimum And 3.453 Inches Maximum
<b>Head Style:</b>	Bevel-conical
<b>Head Diameter:</b>	0.740 Inches Minimum And 0.750 Inches Maximum
<b>Head Height:</b>	0.438 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Width Across Flats:</b>	0.313 Inches Minimum And 0.315 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20007-42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.