

Description

length: 4-13/16" Grip: 4" Thread: 7/16-20, internal wrenching bolt, cadmium plated alloy steel, MS20007 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000764
Minimum Qty (MOQ):	1
NSN:	5306-00-579-4053
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS20007-64 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.812 Inches Minimum
Fastener Length:	4.812 Inches Nominal
Head Style:	Bevel-conical
Head Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.438 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.438 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Nominal Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20007-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.