

**Description**

Fastener Length: 2-5/16", Hole Diameter: ", Thread: 7/16-20, Head Width: 5/16", Thread Length: 53/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20007H24
Minimum Qty (MOQ):	1
NSN:	5306-00-276-8329
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS20007H24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.787 Inches Minimum And 0.837 Inches Maximum
<b>Fastener Length:</b>	2.297 Inches Minimum And 2.327 Inches Maximum
<b>Head Diameter:</b>	0.740 Inches Minimum And 0.750 Inches Maximum
<b>Head Height:</b>	0.438 Inches Nominal
<b>Hole Diameter:</b>	0.062 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Width Across Flats:</b>	0.313 Inches Minimum And 0.315 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Round Longitudinal Hole
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20007H24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.