

Description

Hex head, internal wrenching

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2000816
Minimum Qty (MOQ):	2
NSN:	5306-01-492-8476
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS20008-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.787 Inches Minimum And 0.827 Inches Maximum
Fastener Length:	1.787 Inches Minimum And 1.827 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.818 Inches Minimum And 0.828 Inches Maximum
Head Height:	0.500 Inches Nominal
Internal Drive Style:	Hexagon
End Item Identification:	C5 Acft
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.