

# P/N MS20008-24

## **Description**

Fastener Length: 2-5/16", Thread: 1/2-20, Head Width: 3/8", Thread Length: 3/4",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2000824

Minimum Qty (MOQ):

NSN: 5306-00-206-9651

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20008-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.812 Inches Nominal
Fastener Length:	2.297 Inches Minimum And 2.327 Inches Maximum
Head Diameter:	0.818 Inches Minimum And 0.828 Inches Maximum
Head Height:	0.500 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.3755 Inches Minimum And 0.3785 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

### **How to Order**

Order this internal wrenching bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-24">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-24</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-24">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-24</a> and selecting the