

Description

Fastener Length: 2-29/64", Thread: 1/2-20, Head Width: 3/8", Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2000826 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-049-5323 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS20008-26 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.788 Inches Minimum And 0.838 Inches Maximum |
| Fastener Length: | 2.423 Inches Minimum And 2.453 Inches Maximum |
| Head Style: | Bevel-conical |
| Head Diameter: | 0.818 Inches Minimum And 0.828 Inches Maximum |
| Head Height: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.500 Inches |
| Width Across Flats: | 0.375 Inches Minimum And 0.378 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.