

Description

Fastener Length: 2-15/16", Thread: 1/2-20, Head Width: 3/8", Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000834
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-207-4093
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS20008-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.812 Inches Nominal
Fastener Length:	2.938 Inches Nominal
Head Diameter:	0.818 Inches Minimum And 0.828 Inches Maximum
Head Height:	0.500 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.3755 Inches Minimum And 0.3785 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.