

## Description

Fastener Length: 3-3/4", Thread: 1/2-20, Head Width: 3/8", Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS2000848
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-637-9898
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS20008-48 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.812 Inches Nominal
<b>Fastener Length:</b>	3.812 Inches Nominal
<b>Head Diameter:</b>	0.818 Inches Minimum And 0.828 Inches Maximum
<b>Head Height:</b>	0.500 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Width Across Flats:</b>	0.3755 Inches Minimum And 0.3785 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.