

# P/N MS20008H10

## **Description**

Fastener Length: 1-7/16", Thread: 1/2-20, Head Width: 3/8", Thread Length: 13/16", drilled, MS20008 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: MS20008H10

Minimum Qty (MOQ):

NSN: 5306-00-576-0894

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20008H10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.813 Inches Nominal
Fastener Length:	1.438 Inches Nominal
Head Style:	Bevel-conical Service Control of the
Head Diameter:	0.818 Inches Minimum And 0.828 Inches Maximum
Head Height:	0.500 Inches Nominal
Hole Diameter:	0.055 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.3755 Inches Minimum And 0.3785 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unf

### **How to Order**

Order this internal wrenching bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008H10">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008H10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.