

# P/N MS20008H46

Military-Fasteners.com

#### Description

Fastener Length: 3-45/64", Hole Diameter: ", Thread: 1/2-20, Head Width: 3/8", Thread Length: 53/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS20008H46
Minimum Qty (MOQ):	2
NSN:	5306-00-207-4091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS20008H46 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.788 Inches Minimum And 0.838 Inches Maximum
Fastener Length:	3.673 Inches Minimum And 3.703 Inches Maximum
Head Style:	Bevel-conical
Head Height:	0.500 Inches Nominal
Hole Diameter:	0.062 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.376 Inches Minimum And 0.379 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

### How to Order

Order this internal wrenching bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20008H46</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.