

**Description**

Fastener Length: 3-3/16", Thread: 5/8-18, Head Width: 1/2", Thread Length: 15/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20010H36
Minimum Qty (MOQ):	1
NSN:	5306-00-584-6675
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS20010H36 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.938 Inches Nominal
<b>Fastener Length:</b>	3.173 Inches Minimum And 3.203 Inches Maximum
<b>Head Style:</b>	Bevel-conical
<b>Head Diameter:</b>	1.040 Inches Minimum And 1.050 Inches Maximum
<b>Head Height:</b>	0.625 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.625 Inches
<b>Width Across Flats:</b>	0.5005 Inches Minimum And 0.5035 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20010H36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.