

Description

Fastener Length: 3-3/16", Thread: 5/8-18, Head Width: 1/2", Thread Length: 15/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20010H36
Minimum Qty (MOQ):	1
NSN:	5306-00-584-6675
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS20010H36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.938 Inches Nominal
Fastener Length:	3.173 Inches Minimum And 3.203 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	1.040 Inches Minimum And 1.050 Inches Maximum
Head Height:	0.625 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.625 Inches
Width Across Flats:	0.5005 Inches Minimum And 0.5035 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20010H36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.