

Description

Fastener Length: 3-3/16", Thread: 5/8-18, Head Width: 1/2", Thread Length: 15/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS20010H36 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-00-584-6675 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS20010H36 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.938 Inches Nominal |
| Fastener Length: | 3.173 Inches Minimum And 3.203 Inches Maximum |
| Head Style: | Bevel-conical |
| Head Diameter: | 1.040 Inches Minimum And 1.050 Inches Maximum |
| Head Height: | 0.625 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.625 Inches |
| Width Across Flats: | 0.5005 Inches Minimum And 0.5035 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20010H36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.