

P/N MS20010H46

Description

Fastener Length: 3-51/64", Hole Diameter: 1/16", Thread: 5/8-18, Head Width: 1/2", Thread Length: 59/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Minimum Qty (MOQ):	1 EA
SKU / Model:	MS20010H46

NSN: 5306-00-639-2955

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS20010H46 Specifications

Thread Direction: Right-hand Thread Length: 0.912 Inches Minimum And 0.962 Inches Maximum Fastener Length: 3.797 Inches Minimum And 3.827 Inches Maximum Head Style: Bevel-conical Head Diameter: 1.040 Inches Minimum And 1.050 Inches Maximum Head Height: 0.625 Inches Nominal Head Height: 0.625 Inches Nominal Hole Diameter: 0.055 Inches Nominal Hole Diameter: 0.055 Inches Nominal Hole Diameter: 0.625 Inches Nominal Hole Diameter: 0.625 Inches Nominal Hole Diameter: 0.625 Inches Minimum And 0.503 Inches Maximum Hole Diameter: 0.625 Inches Word Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Sp		
Frastener Length: 0.912 Inches Minimum And 0.962 Inches Maximum Frastener Length: 3.797 Inches Minimum And 3.827 Inches Maximum Head Style: Bevel-conical Head Diameter: 1.040 Inches Minimum And 1.050 Inches Maximum Held Height: 0.625 Inches Nominal Hole Diameter: 0.055 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.625 Inches Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Quantity: 4 Flore Quantity: 4 Flore Quantity: 4 Flore Opilied Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mile-s6039 Mil Spec 3rd Material Response Overall Or Mile-s6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil	Thread Class:	3a
Fastener Length: 3.797 Inches Minimum And 3.827 Inches Maximum Head Style: Bevel-conical Head Diameter: 1.040 Inches Minimum And 1.050 Inches Maximum Head Height: 0.625 Inches Nominal Hole Diameter: 0.055 Inches Nominal Hole Diameter: 0.625 Inches Nominal Hole Quantity: 0.625 Inches Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall More Treatment Document And Classification: Qcp-4-16.ty 2 C1 2 Fed Spec Single Treatment Response Overall	Thread Direction:	Right-hand
Head Diameter: 1.040 Inches Minimum And 1.050 Inches Maximum Head Height: 0.625 Inches Nominal Hole Diameter: 0.055 Inches Nominal Hole Diameter: 0.055 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.625 Inches Wildth Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Wildth Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mils-5-626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Length:	0.912 Inches Minimum And 0.962 Inches Maximum
Head Diameter: 1.040 Inches Minimum And 1.050 Inches Maximum Head Height: 0.625 Inches Nominal Hole Diameter: 0.055 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.625 Inches Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Quantity: 4 Hole Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Fastener Length:	3.797 Inches Minimum And 3.827 Inches Maximum
Head Height: 0.625 Inches Nominal Hole Diameter: 0.055 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.625 Inches Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Ma	Head Style:	Bevel-conical Service Control of the
Hole Diameter: 0.055 Inches Nominal Internal Drive Style: Hexagon 0.625 Inches Nominal Thread Diameter: 0.625 Inches Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overa	Head Diameter:	1.040 Inches Minimum And 1.050 Inches Maximum
Internal Drive Style: Nominal Thread Diameter: 0.625 Inches Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: Hardness Rating: 4.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall And Classification:	Head Height:	0.625 Inches Nominal
Nominal Thread Diameter: 0.625 Inches Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5	Hole Diameter:	0.055 Inches Nominal
Width Across Flats: 0.500 Inches Minimum And 0.503 Inches Maximum Hole Quantity: 4 Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Oq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Hexagon
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.625 Inches
Hole Type: Drilled Thread Quantity Per Inch: 18 Minimum Tensile Strength: Hardness Rating: Hole Configuration Style: Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Cadmium Overall And Classification: Drilled 18 160000 Pounds Per Square Inch Material Document Openation Style: Round Longitudinal Hole Steel Comp 4140 Overall And 40.0 Rockwell C Maximum Overall And Classification: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Width Across Flats:	0.500 Inches Minimum And 0.503 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Gadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Hole Quantity:	4
Minimum Tensile Strength: Hardness Rating: Hardness Rating: Hole Configuration Style: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Re	Hole Type:	Drilled
Hardness Rating: Hole Configuration Style: Round Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	18
Hole Configuration Style: Round Longitudinal Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Ma	Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Over	Hole Configuration Style:	Round Longitudinal Hole
Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Material Document And Classification:	
Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall And Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20010H46 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.