

Description

Fastener Length: 53/64", Thread: 10-32, Thread Length: 15/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS200333
Minimum Qty (MOQ):	5
NSN:	5306-00-515-9279
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20033-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.390 Inches Minimum And 0.469 Inches Maximum
Fastener Length:	0.781 Inches Minimum And 0.828 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.359 Inches Minimum And 0.391 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hardness Rating:	27.0 Rockwell C Minimum Overall And 37.0 Rockwell C Maximum Overall
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20033-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.