

Description

Fastener Length: 59/64", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS200334
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-827-1971
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS20033-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.422 Inches Minimum
Fastener Length:	0.922 Inches Nominal
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.500 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	110000 Pounds Per Square Inch
Minimum Yield Strength:	90000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Mil-b-7874 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Special Test Features:	Rupture Strength At 1200 Deg. F Shall Not Be Less Than 47000 Psi In 100 Hours
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20033-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.