

**Description**

Fastener Length: 59/64", Thread: 10-32, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS200334                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-827-1971                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS20033-4 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.422 Inches Minimum  |
| <b>Fastener Length:</b>                      | 0.922 Inches Nominal  |
| <b>Head Style:</b>                           | Hexagon   |
| <b>Head Height:</b>                          | 0.109 Inches Minimum And 0.141 Inches Maximum                                 |
| <b>Width Between Flats:</b>                  | 0.365 Inches Minimum And 0.377 Inches Maximum                                 |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches  |
| <b>Grip Length:</b>                          | 0.500 Inches Nominal  |
| <b>Features Provided:</b>                    | Finished Head   |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Minimum Tensile Strength:</b>             | 110000 Pounds Per Square Inch   |
| <b>Minimum Yield Strength:</b>               | 90000 Pounds Per Square Inch  |
| <b>Material:</b>                             | Steel Corrosion Resisting Overall   |
| <b>Material Document And Classification:</b> | Mil-b-7874 Mil Spec Single Material Response Overall                          |
| <b>Surface Treatment:</b>                    | Passivate Overall   |
| <b>Special Test Features:</b>                | Rupture Strength At 1200 Deg. F Shall Not Be Less Than 47000 Psi In 100 Hours |
| <b>Thread Series Designator:</b>             | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20033-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.