



Military-Fasteners.com

P/N MS20033-4

## Description

Fastener Length: 59/64", Thread: 10-32, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS200334
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-827-1971
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS20033-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.422 Inches Minimum
<b>Fastener Length:</b>	0.922 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.109 Inches Minimum And 0.141 Inches Maximum
<b>Width Between Flats:</b>	0.365 Inches Minimum And 0.377 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.500 Inches Nominal
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	110000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	90000 Pounds Per Square Inch
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Mil-b-7874 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Special Test Features:</b>	Rupture Strength At 1200 Deg. F Shall Not Be Less Than 47000 Psi In 100 Hours
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20033-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.