

Description

length: 1-1/64", grip: 1/2", thread: 1/4-28, hex head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS200344
Minimum Qty (MOQ):	10
NSN:	5306-00-877-5556
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20034-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.516 Inches Minimum
Fastener Length:	1.016 Inches Nominal
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.500 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	110000 Pounds Per Square Inch
Minimum Yield Strength:	90000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Mil-b-7874 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Special Test Features:	Rapture Strength At 2200 Deg F Shall Not Be Less Than 47000 Psi In 100 Hours
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20034-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.