

Description

length: 1-9/64", grip: 5/8", thread: 1/4-28, hex head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS200345
Minimum Qty (MOQ):	10
NSN:	5306-00-889-3007
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20034-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.484 Inches Minimum And 0.563 Inches Maximum
Fastener Length:	1.125 Inches Minimum And 1.172 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.609 Inches Minimum And 0.641 Inches Maximum
Features Provided:	Unfinished Head
Thread Quantity Per Inch:	28
Hardness Rating:	27.0 Rockwell C Minimum Overall And 37.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20034-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.