

**Description**

Fastener Length: 1-21/32", Thread: 3/8-24, Thread Length: 41/64", MS20036 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2003610
Minimum Qty (MOQ):	5
NSN:	5306-00-826-5959
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N MS20036-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.640 Inches Minimum And 0.719 Inches Maximum
<b>Fastener Length:</b>	1.656 Inches Minimum And 1.703 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.203 Inches Minimum And 0.235 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.565 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.984 Inches Minimum And 1.016 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Hardness Rating:</b>	27.0 Rockwell C Minimum Overall And 37.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20036-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.