

Description

Fastener Length: 1-21/32", Thread: 3/8-24, Thread Length: 41/64", MS20036 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2003610
Minimum Qty (MOQ):	5
NSN:	5306-00-826-5959
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS20036-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.640 Inches Minimum And 0.719 Inches Maximum
Fastener Length:	1.656 Inches Minimum And 1.703 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.984 Inches Minimum And 1.016 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hardness Rating:	27.0 Rockwell C Minimum Overall And 37.0 Rockwell C Maximum Overall
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20036-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.