

Description

Fastener Length: 1-35/64", Thread: 3/8-24, Thread Length: 43/64", MS20036 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS200367 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-823-5900 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS20036-7 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.672 Inches Minimum |
| Fastener Length: | 1.547 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.203 Inches Minimum And 0.235 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.565 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.875 Inches Nominal |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 110000 Pounds Per Square Inch |
| Minimum Yield Strength: | 90000 Pounds Per Square Inch |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Mil-b-7874 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Special Test Features: | Rapture Strength At 1200 Deg F Shall Not Be Less Than 47000 Psi In 100 Hrs |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20036-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.