



Military-Fasteners.com

P/N MS20038-4

Description

Fastener Length: 1-21/64", Thread: 1/2-20, Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS200384
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-842-1237
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20038-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.828 Inches Minimum
Fastener Length:	1.328 Inches Nominal
Head Style:	Hexagon
Head Height:	0.265 Inches Minimum And 0.297 Inches Maximum
Width Between Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.500 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	110000 Pounds Per Square Inch
Minimum Yield Strength:	90000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Mil-b-7874 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Special Test Features:	Rapture Strength An 1200 Deg F Shall Not Be Less Than 47000 Psi In 100 Hrs
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20038-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.