

P/N MS20073-03-02

Description

Fastener Length: 21/64", Hole Diameter: 5/64", Thread: 10-32, Thread Length: 1/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS200730302

Minimum Qty (MOQ): 20

NSN: 5306-00-145-6954

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N MS20073-03-02 Specifications

Thread Class: 3a Thread Length: 0.250 Inches Minimum And 0.329 Inches Maximum Thread Length: 0.328 Inches Minimum And 0.375 Inches Maximum Thread Length: 0.328 Inches Minimum And 0.375 Inches Maximum Thread Style: Hexagon Thread Length: 0.172 Inches Minimum And 0.203 Inches Maximum Thread Length: 0.367 Inches Minimum And 0.203 Inches Maximum Thread Diameter: 0.367 Inches Minimum And 0.376 Inches Maximum Thread Diameter: 0.190 Inches Thread Diameter: 0.364 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.078 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.376 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.376 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.376 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.376 Inches Maximum Thread Diameter: 0.365 Inches Minimum And 0.376 Inches Maximum Thread Diameter: 0.365 Inches Maximum Thread Diameter:
Chread Length: 0.250 Inches Minimum And 0.329 Inches Maximum 0.328 Inches Minimum And 0.375 Inches Maximum Dead Style: Hexagon Dead Height: 0.172 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.070 Inches Minimum And 0.376 Inches Maximum Dominal Thread Diameter: 0.070 Inches Nominal Dominal Thread Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum Double Quantity: 0.046 Inches Minimum And 0.078 Inches Maximum Double Type: Drilled Dri
Asstener Length: 0.328 Inches Minimum And 0.375 Inches Maximum Head Style: Hexagon Head Height: 0.172 Inches Minimum And 0.203 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Hole Diameter: 0.070 Inches Nominal Hominal Thread Diameter: 0.190 Inches Firip Length: 0.046 Inches Minimum And 0.078 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Finished Head Head Quantity Per Inch: 32 Hinimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Head Style: Hexagon Jead Height: 0.172 Inches Minimum And 0.203 Inches Maximum John Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum John Between Flats: 0.070 Inches Nominal John Inches Volle Diameter: 0.190 Inches John Inches Minimum And 0.078 Inches Maximum John Quantity: 6 John Colle Type: Drilled John Col
Head Height: 0.172 Inches Minimum And 0.203 Inches Maximum Vidth Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Jole Diameter: 0.070 Inches Nominal Jominal Thread Diameter: 0.190 Inches Jori Length: 0.046 Inches Minimum And 0.078 Inches Maximum Jole Quantity: 6 Jole Quantity: 6 Jole Type: Drilled Jori Lead Quantity Per Inch: 32 Jori Length: 125000 Pounds Per Square Inch Jori Length: 125000 Pounds Per Square Inch Jori Length: 125000 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Vidth Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Jole Diameter: 0.070 Inches Nominal Jominal Thread Diameter: 0.190 Inches Jorip Length: 0.046 Inches Minimum And 0.078 Inches Maximum Jole Quantity: 6 Jole Quantity: 6 Jorilled Joril
Hole Diameter: 0.070 Inches Nominal 0.190 Inches 0.190 Inches 0.046 Inches Minimum And 0.078 Inches Maximum 0.046 Inches Inche
Iominal Thread Diameter: 0.190 Inches Grip Length: 0.046 Inches Minimum And 0.078 Inches Maximum Iole Quantity: 6 Iole Type: Drilled Finished Head Thread Quantity Per Inch: 32 Inimum Tensile Strength: 125000 Pounds Per Square Inch Idiardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Grip Length: 0.046 Inches Minimum And 0.078 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Finished Head Thread Quantity Per Inch: 32 Hinimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Quantity: 6 Hole Type: Drilled Finished Head Finished Head Finished Provided: 32 Finished Head Finished H
Hole Type: Peatures Provided: Finished Head Thread Quantity Per Inch: Finished Finished Head Alinimum Tensile Strength: Finished Head 125000 Pounds Per Square Inch 125000 Pounds Per Square Inch 125000 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Finished Head Chread Quantity Per Inch: Inimum Tensile Strength: I 25000 Pounds Per Square Inch I ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Jardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Alinimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
lardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
lole Configuration Style: Hexagon Longitudinal Hole
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Occument And Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:
hread Series Designator: Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS20073-03-02 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.