

P/N MS20073-04-04

Description

length: 19/32", grip: 1/16", thread: 1/4-28, drilled head, fine thread

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS200730404

Minimum Qty (MOQ): 10

NSN: 5306-00-151-1084

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS20073-04-04 Specifications

hread Direction: Right-hand hread Length: 0.499 Inches Minimum And 0.578 Inches Maximum astener Length: 0.578 Inches Minimum And 0.625 Inches Maximum lead Style: Hexagon lead Height: 0.203 Inches Minimum And 0.439 Inches Maximum lidth Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum lidth Between Flats: 0.570 Inches Nominal look Diameter: 0.070 Inches Nominal look Diameter: 0.505 Inches look Diameter: 0.505 Inches look Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum look Quantity: 6 look Type: Drilled leatures Provided: Finished Head hread Quantity Per Inch: 28 linimum Tensile Strength: 125000 Pounds Per Square Inch lardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall look Configuration Style: Hexagon Flats laterial: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Mills-5626 Mil Spec 1st Material Response Overall Or Mills-6049 Mil Spec 2nd Material Response Overall Or Mills-6050 Mil Spec 3rd Material Response Overall Or Mills-6098 Mil Spec 4th Material Response Overall Or Mills-6758 Mil Spec 5th Material Response Overall Or Mills-6758 Mill Spec 5th Material Response Overall Or Mills-6758 Mills Spec 5th Material Response Overall Or Mills-		
Aread Length: astener Length: bead Style: lead Style: lead Style: lead Height: 0.203 Inches Minimum And 0.234 Inches Maximum lead Height: 0.203 Inches Minimum And 0.234 Inches Maximum lidith Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum lidith Between Flats: 0.070 Inches Nominal loomlal Thread Diameter: 0.070 Inches Nominal loomlal Thread Diameter: 0.045 Inches Minimum And 0.078 Inches Maximum loole Quantity: 6 lole Quantity: 6 lole Quantity: 6 lole Quantity: 6 lole Type: 0 Drilled leatures Provided: Inimum Tensile Strength: 125000 Pounds Per Square Inch lardness Rating: 106 Configuration Style: 106 Leagun Flats Laterial: 108 Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil S	Thread Class:	3a
lead Style: Hexagon lead Height: 0.203 Inches Minimum And 0.234 Inches Maximum loid Bed Height: 0.203 Inches Minimum And 0.234 Inches Maximum loid Biameter: 0.070 Inches Nominal And 0.439 Inches Maximum loid Diameter: 0.070 Inches Nominal loid Diameter: 0.250 Inches loid Diameter: 0.250 Inches loid Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches loid Quantity: 0.500 Inches loid Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches loid Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum loid Quantity: 0.500 Inches Minimum And 0.078 Inches Minimum loid Quantity: 0.500 Inches Minimum And 0.078 I	Thread Direction:	Right-hand
lead Style: Hexagon lead Height: 0.203 Inches Minimum And 0.234 Inches Maximum lobe Diameter: 0.430 Inches Minimum And 0.439 Inches Maximum lobe Diameter: 0.250 Inches Nominal lobe Diameter: 0.250 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Minimum And 0.078 Inches Maximum lobe Quantity: 0.500 Inches Maximum Overall And 32.0 Rockwell C Maximum Overall Or Steel Comp 8735 Overall Or Steel Comp 4030 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Materia	Thread Length:	0.499 Inches Minimum And 0.578 Inches Maximum
lead Height: 0.203 Inches Minimum And 0.234 Inches Maximum 0.430 Inches Minimum And 0.439 Inches Maximum 1.010 Diameter: 0.070 Inches Nominal 1.010 Diameter: 0.250 Inches 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum And 0.078 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum 1.010 Diameter: 0.046 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum 1.010 Diameter: 0.046 Inches Maximum 1.010 Diameter: 0.046 Inches Minimum 1.010 Diameter: 0.046 Inches Maximum 1.010 Diameter: 0.046 Inches Maximum 1.010 Diameter: 0.046 Inches	Fastener Length:	0.578 Inches Minimum And 0.625 Inches Maximum
Add the Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum 0.070 Inches Nominal 0.070 Inches Nominal 0.250 Inches 0.250 Inches 0.250 Inches 0.250 Inches 0.046 Inches Minimum And 0.078 Inches Maximum 0.046 Inches Maximum And 0.078	Head Style:	Hexagon
loie Diameter: 0.070 Inches Nominal 0.250 Inches 0.046 Inches Minimum And 0.078 Inches Maximum 0.060 Quantity: 0.046 Inches Minimum And 0.078 Inches Maximum 0.060 Quantity: 0	Head Height:	0.203 Inches Minimum And 0.234 Inches Maximum
lowinal Thread Diameter: 0.250 Inches 0.046 Inches Minimum And 0.078 Inches Maximum 0.06e Quantity: 6 Orilled Inches Provided: Inished Head Inished Quantity Per Inch: Indimum Tensile Strength: Indiana	Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
O.46 Inches Minimum And 0.078 Inches Maximum	Hole Diameter:	0.070 Inches Nominal
tole Quantity: 6 tole Type: Drilled eatures Provided: Finished Head hread Quantity Per Inch: 28 tinimum Tensile Strength: 125000 Pounds Per Square Inch lardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall tole Configuration Style: Hexagon Flats taterial: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall urface Treatment: Cadmium Overall And Chromate Overall ocument And Qq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.250 Inches
prilled finished Head hread Quantity Per Inch: lardness Rating: lole Configuration Style: laterial: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall laterial Document And lassification: Will-s-6626 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Urface Treatment: Urface Treatment Locument And	Grip Length:	0.046 Inches Minimum And 0.078 Inches Maximum
eatures Provided: hread Quantity Per Inch: 28 Ilinimum Tensile Strength: 125000 Pounds Per Square Inch Idardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall urface Treatment: urface Treatment occument And Qq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Hole Quantity:	6
hread Quantity Per Inch: 28 Inimum Tensile Strength: 125000 Pounds Per Square Inch Idardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Idea Configuration Style: Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Idea Comp 4037 Overall Idea Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Asson Std 6th Material Response Overall Urface Treatment: Cadmium Overall And Chromate Overall Urface Treatment Occument And Oq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Ininimum Tensile Strength: Ininimum Tensile Stre	Features Provided:	Finished Head
26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall urface Treatment: Cadmium Overall And Chromate Overall Oq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	28
Hexagon Flats Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall urface Treatment occument And Qq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall urface Treatment ocument And Oq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Hole Configuration Style:	Hexagon Flats
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall urface Treatment: urface Treatment ocument And Qq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Material:	
urface Treatment cocument And Qq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn
Occument And Qq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
iassification.	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 31 3 Fed Spec All Treatment Responses Overall
hread Series Designator: Unf	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS20073-04-04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.