

P/N MS20073-04-06

Description

length: 25/32", grip: 1/4", thread: 1/4-28n drilled head, fine thread

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS200730406

Minimum Qty (MOQ): 10

NSN: 5306-00-754-3048

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N MS20073-04-06 Specifications

Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.640 Inches Minimum And 0.719 Inches Maximum Tastener Length: 0.781 Inches Minimum And 0.828 Inches Maximum Tastener Length: 0.781 Inches Minimum And 0.828 Inches Maximum Tastener Length: 0.203 Inches Minimum And 0.824 Inches Maximum Tastener Plats: 0.203 Inches Minimum And 0.234 Inches Maximum Tastener Plats: 0.430 Inches Minimum And 0.439 Inches Maximum Tastener Plats: 0.430 Inches Minimum And 0.439 Inches Maximum Tastener Plats: 0.070 Inches Nominal Tastener Plats: 0.250 Inches Tastener Plats: 0.109 Inches Minimum And 0.141 Inches Maximum Tastener Plats: 0.500 Inches Minimum A
thread Length: 0.640 Inches Minimum And 0.719 Inches Maximum lead Style: Hexagon lead Height: 0.203 Inches Minimum And 0.234 Inches Maximum lole Diameter: 0.430 Inches Minimum And 0.439 Inches Maximum lole Diameter: 0.070 Inches Nominal lominal Thread Diameter: 0.250 Inches lole Quantity: 0.109 Inches Minimum And 0.141 Inches Maximum lole Quantity: 0.109 Inches Minimum And 0.141 Inches Maximum lole Quantity: 0.100 Inches Minimum And 0.141 Inches Maximum lole Quantity: 0.100 Inches Minimum And 0.141 Inches Maximum lole Quantity Per Inch: 0.100 Inches Minimum And 0.141 Inches Maximum lole Type: 0.100 Inches Minimum
Asstener Length: 0.781 Inches Minimum And 0.828 Inches Maximum Alead Style: Hexagon Alead Height: 0.203 Inches Minimum And 0.234 Inches Maximum Aloie Diameter: 0.430 Inches Minimum And 0.439 Inches Maximum Aloie Diameter: 0.070 Inches Nominal Alominal Thread Diameter: 0.250 Inches Airip Length: 0.109 Inches Minimum And 0.141 Inches Maximum Aloie Quantity: 6 Aloie Type: Drilled Aleatures Provided: Finished Head Aloin And Quantity Per Inch: 28 Aloinimum Tensile Strength: 125000 Pounds Per Square Inch
Head Style: Hexagon Jead Height: 0.203 Inches Minimum And 0.234 Inches Maximum Jidth Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Jole Diameter: 0.070 Inches Nominal Jominal Thread Diameter: 0.250 Inches Jorip Length: 0.109 Inches Minimum And 0.141 Inches Maximum Jole Quantity: 6 Jole Type: Drilled Joribed Head Joribed Quantity Per Inch: 28 Joribinum Tensile Strength: 125000 Pounds Per Square Inch
Nidth Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Nole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.250 Inches Nominal Thread Diameter: 0.109 Inches Minimum And 0.141 Inches Maximum Nole Quantity: 6 Nole Quantity: 6 Note Type: Drilled Neatures Provided: Finished Head Note Advantity Per Inch: 28 Note Advantity Per Inch: 125000 Pounds Per Square Inch
Vidth Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Jole Diameter: 0.070 Inches Nominal Jominal Thread Diameter: 0.250 Inches Jorip Length: 0.109 Inches Minimum And 0.141 Inches Maximum Jole Quantity: 6 Jorilled Jor
lole Diameter: 0.070 Inches Nominal 0.250 Inches 0.250 Inches 0.250 Inches 0.109 Inches Minimum And 0.141 Inches Maximum 0.101 Quantity: 6 lole Type: Drilled Finished Head Provided: Finished Head Provided: 28 Inimum Tensile Strength: 125000 Pounds Per Square Inch
Iominal Thread Diameter: 0.250 Inches Irip Length: 0.109 Inches Minimum And 0.141 Inches Maximum Iole Quantity: 6 Iole Type: Drilled Finished Head Thread Quantity Per Inch: 28 Inimum Tensile Strength: 125000 Pounds Per Square Inch
Grip Length: 0.109 Inches Minimum And 0.141 Inches Maximum Gole Quantity: 6 Gole Type: Drilled Finished Head Finished Head Finished Quantity Per Inch: 28 Finished Strength: 125000 Pounds Per Square Inch
lole Quantity: 6 lole Type: Drilled leatures Provided: Finished Head lhread Quantity Per Inch: 28 linimum Tensile Strength: 125000 Pounds Per Square Inch
lole Type: Drilled Finished Head Chread Quantity Per Inch: 28 Inimum Tensile Strength: 125000 Pounds Per Square Inch
reatures Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch
Thread Quantity Per Inch: 28 Inimum Tensile Strength: 125000 Pounds Per Square Inch
Minimum Tensile Strength: 125000 Pounds Per Square Inch
lardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Iole Configuration Style: Hexagon Longitudinal Hole
Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall
Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall
Surface Treatment: Cadmium Overall
Surface Treatment Occument And Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall Classification:
hread Series Designator: Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS20073-04-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.