

P/N MS20073-04-11

Description

Fastener Length: 1-3/16", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 37/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS200730411

Minimum Qty (MOQ): 10

NSN: 5306-00-807-6894

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS20073-04-11 Specifications

Thread Direction: Right-hand Thread Length: 0.500 Inches Minimum And 0.578 Inches Maximum Fastener Length: 1.14 Inches Minimum And 1.188 Inches Maximum Head Style: Hexagon Head Height: 0.203 Inches Minimum And 0.234 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Width Between Flats: 0.070 Inches Nominal Nominal Thread Diameter: 0.050 Inches Grip Length: 0.609 Inches Minimum And 0.641 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 125000 Poun		
Tread Length: 0.500 Inches Minimum And 0.578 Inches Maximum Faster Length: 1.14 Inches Minimum And 1.188 Inches Maximum Head Style: Hexagon Head Height: 0.203 Inches Minimum And 0.234 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Width Between Flats: 0.407 Inches Nominal Nominal Thread Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.609 Inches Minimum And 0.641 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Material Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Op-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Americal Classification: Cadmium Overall And Chromate Overall Classification: Cadmium Overall And Chromate Overa	Thread Class:	3a
Fastener Length: Head Style: Head Height: D. 203 Inches Minimum And 0.234 Inches Maximum Width Between Flats: O. 303 Inches Minimum And 0.234 Inches Maximum Width Between Flats: O. 305 Inches Minimum And 0.439 Inches Maximum Width Between Flats: O. 307 Inches Minimum And 0.439 Inches Maximum Hole Diameter: O. 250 Inches Grip Length: O. 609 Inches Minimum And 0.641 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Freatures Provided: Finished Head Thread Quantity Per Inch: Bardinam Tensile Strength: Hardness Rating: C. 80. Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Heagon Longitudinal Hole Material: Steel Comp 4037 Overall Material Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment: Courage And Surface And Classification: Cadmium Overall And Chromate Overall Classification: Cadmium Overall And School Courage Cou	Thread Direction:	Right-hand
Head Style: Head Height: 0.203 Inches Minimum And 0.234 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Hole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.250 Inches Minimum And 0.641 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 25000 Pounds Per Square Inch Hardness Rating: 26.00 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Cadmium Overall And Chromate Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Ocument And Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Cadmium Overall And Chromate Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p-416 Ty 2 Cl 3 Fed Spec All Treatment Response Overall Classification: Q-p	Thread Length:	0.500 Inches Minimum And 0.578 Inches Maximum
Head Height: 0.203 Inches Minimum And 0.234 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Hole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.250 Inches Grip Length: 0.609 Inches Minimum And 0.641 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 45.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Material Document And Classification: Stufface Treatments Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Ocument And Classification:	Fastener Length:	1.141 Inches Minimum And 1.188 Inches Maximum
Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Hole Diameter: 0.250 Inches Grip Length: 0.609 Inches Minimum And 0.641 Inches Maximum Hole Quantity: 6 Hole Quantity: 6 Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-5-6256 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Sturface Treatment: Cadmium Overall And Chromate Overall Classification: Cadmium Overall And Chromate Overall	Head Style:	Hexagon
Hole Diameter: 0.070 Inches Nominal O.250 Inches O.250 In	Head Height:	0.203 Inches Minimum And 0.234 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.609 Inches Minimum And 0.641 Inches Maximum 6 Hole Quantity: 6 Hole Type: Prinished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Headers Agon Longitudinal Hole Material: Material: Minimum Tensile Steength: Minimum Tensile Strength: Accompany overall or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Minis-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Length: 0.609 Inches Minimum And 0.641 Inches Maximum Hole Quantity: 6 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response O	Hole Diameter:	0.070 Inches Nominal
Hole Quantity: 6 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Strip Cadmium Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Cadmium Overall Creatment Responses Overall Creatment Response Ove	Nominal Thread Diameter:	0.250 Inches
Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Longitudinal Hole Hexagon Longitudinal Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Wil-s-626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Ocument And Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Grip Length:	0.609 Inches Minimum And 0.641 Inches Maximum
Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Longitudinal Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Mater	Hole Quantity:	6
Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Longitudinal Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Hole Type:	Drilled
Minimum Tensile Strength: Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hexagon Longitudinal Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Features Provided:	Finished Head
Hardness Rating: Hole Configuration Style: Hexagon Longitudinal Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	28
Hexagon Longitudinal Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Steel Comp 4037 Overall Material Document And Classification: Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Hole Configuration Style:	Hexagon Longitudinal Hole
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spe	Material:	
Surface Treatment Document And Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn
Document And Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS20073-04-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.