

Description


Fastener Length: 1-13/16", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS200730416
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-491-9356
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS20073-04-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.489 Inches Minimum And 0.509 Inches Maximum
Fastener Length:	1.765 Inches Minimum And 1.812 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.234 Inches Minimum And 1.266 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20073-04-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.