

Description

Fastener Length: 19/32", Hole Diameter: 5/64", Thread: 5/16-24, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS200730504
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-150-9148
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20073-05-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.517 Inches Minimum And 0.593 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.640 Inches Maximum
Head Style:	Hexagon
Head Height:	0.266 Inches Minimum And 0.297 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.501 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.047 Inches Minimum And 0.077 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 8740 Overall Or Steel Comp 8640 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20073-05-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.