



Military-Fasteners.com

P/N MS20073-05-24

## Description

Fastener Length: 2-17/32", Hole Diameter: 5/64", Thread: 5/16-24, Thread Length: 33/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS200730524                               |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5306-00-150-9285                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS20073-05-24 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.515 Inches Minimum And 0.594 Inches Maximum  |
| <b>Fastener Length:</b>                               | 2.531 Inches Minimum And 2.578 Inches Maximum  |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.266 Inches Minimum And 0.297 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.492 Inches Minimum And 0.501 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.070 Inches Nominal   |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches   |
| <b>Grip Length:</b>                                   | 1.984 Inches Minimum And 2.016 Inches Maximum  |
| <b>Hole Quantity:</b>                                 | 6  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Features Provided:</b>                             | Finished Head  |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Hole Configuration Style:</b>                      | Hexagon Longitudinal Hole  |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type2,class3 Fed Spec All Treatment Responses Overall   |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20073-05-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.