

## P/N MS20074-03-05

## **Description**

length: 21/32", grip: 1/8", thread: 10-24, drilled head, coarse thread, engine bolt

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS200740305

Minimum Qty (MOQ):

NSN: 5306-01-601-1671

ECCN: EAR99







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20074-03-05 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.499 Inches Nominal
Fastener Length:	0.656 Inches Nominal
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.125 Inches Nominal
Thread Quantity Per Inch:	24
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

### **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS20074-03-05">https://military-fasteners.com/bolts/machine+bolts/MS20074-03-05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/MS20074-03-05">https://military-fasteners.com/bolts/machine+bolts/MS20074-03-05</a> and selecting the quantity you