

**Description**

Fastener Length: 1-5/8", Hole Diameter: 1/16", Thread: 10-24,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS200740315                               |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-00-814-0785                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS20074-03-15 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.499 Inches Minimum   |
| <b>Fastener Length:</b>                               | 1.656 Inches Nominal   |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.172 Inches Minimum And 0.203 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.070 Inches Nominal   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 1.125 Inches Nominal   |
| <b>Hole Quantity:</b>                                 | 6  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Features Provided:</b>                             | Finished Head  |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Hole Configuration Style:</b>                      | Hexagon Flats  |
| <b>Material:</b>                                      | Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unc  |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20074-03-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.