

Description

Fastener Length: 3-9/32", Thread: 10-24, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS200740332
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-145-6960
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS20074-03-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Minimum
Fastener Length:	3.281 Inches Nominal
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	2.750 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Special Features:	Six Drilled Holes In Head
Material:	Steel Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS20074-03-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.