

P/N MS20074-04-33

Description

Length: 3-3/8", Hole Diameter: 1/16", Thread: 1/4-20, drilled head, for engine use, MS20074 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS200740433

Minimum Qty (MOQ): 20

NSN: 5306-00-051-0055

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS20074-04-33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
	0.499 Inches Minimum
Thread Length:	
Fastener Length:	3.406 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.875 Inches Nominal
Hole Quantity:	6
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS20074-04-33 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.