

P/N MS20074-06-16

Military-Fasteners.com

Description

Fastener Length: 1-51/64", Hole Diameter: 1/16", Thread: 3/8-16, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	MS200740616
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-855-1253
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS20074-06-16 Specifications

Thread Class:3aThread Direction:Right-handRight-band0.640 Inches MinimumThread Length:0.640 Inches MinimumFastener Length:1.797 Inches NominalHead Style:HexagonHead Height:0.266 Inches Minimum And 0.297 Inches MaximumWidth Between Flats:0.554 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.370 Inches NominalNominal Thread Diameter:0.375 Inches NominalGrip Length:1.125 Inches Nominal
Thread Length:0.640 Inches MinimumFastener Length:1.797 Inches NominalHead Style:HexagonHead Height:0.266 Inches Minimum And 0.297 Inches MaximumWidth Between Flats:0.554 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.375 Inches
Fastener Length:1.797 Inches NominalHead Style:HexagonHead Height:0.266 Inches Minimum And 0.297 Inches MaximumWidth Between Flats:0.554 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.375 Inches
Head Style:HexagonHead Height:0.266 Inches Minimum And 0.297 Inches MaximumWidth Between Flats:0.554 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.375 Inches
Head Height:0.266 Inches Minimum And 0.297 Inches MaximumWidth Between Flats:0.554 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.375 Inches
Width Between Flats: 0.554 Inches Minimum And 0.564 Inches Maximum Hole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.375 Inches
Hole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.375 Inches
Nominal Thread Diameter: 0.375 Inches
Grip Length: 1.125 Inches Nominal
Hole Quantity: 6
Hole Type: Drilled
Features Provided: Finished Head
Thread Quantity Per Inch: 16
Minimum Tensile Strength: 125000 Pounds Per Square Inch
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style: Hexagon Longitudinal Hole
Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Steel Comp 4140 Overall
Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Spec 6th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall Classification: Classification:
Thread Series Designator: Unc

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS20074-06-16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.