

**Description**

Use with cables size: 1/8" and 5/32" and 3/16", bore diameter: 5/16", groove diameter: 3-3/4, lubricated, ball bearing type, flight control, nonmetallic sleeve, MS20220 series pulley

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS202203
Minimum Qty (MOQ):	1
NSN:	3020-00-277-1124
Schedule B:	3926.90.9995
ECCN:	EAR99
National Motor Freight:	127320, Pulleys / Sheaves, noi



\* See page 2 for technical characteristics

# P/N MS20220-3 Specifications

Groove Depth:	0.250 Inches Nominal
Groove Width:	0.275 Inches Nominal
Outside Diameter:	4.255 Inches Nominal
Overall Length:	0.625 Inches Nominal
Bore Diameter:	0.3145 Inches Nominal
Bore Length:	0.625 Inches Nominal
Groove Radius:	0.097 Inches Nominal
Material And Location:	Fabric Overall
Face Width:	0.422 Inches Nominal
Design Form:	Plain
Bore Type:	Straight
Bearings:	Included
Groove Quantity:	1
Counterbore Feature:	Not Included
Bearing Quantity:	1
Keying Facility:	Not Included
Split Hub Feature:	Not Included
Lightening Hole:	Not Included
Integral Cooling Vane:	Not Included
Groove Shape:	U
Bore Feature:	Included
Bearing Type:	Ball
Hub End Outside Diameter And Location:	0.515 Inches Nominal Both Ends
Distance From Outside Flange/rim To Hub End And Location:	0.101 Inches Nominal Both Ends
Special Features:	If Requisition Is Not For Fms, Overseas Shipments, Naval Vessels, Priority Codes 1,2, Or 3, Or Individual Requisitions Over 25000 Dollars, Then Direct Vendor Delivery Nsn 3020-01-391-0853 Is Available At 15.7% Discount.
Style Designator:	Plain

## How to Order

Order this groove pulley from our inventory online by visiting <https://military-fasteners.com/pulleys/groove+pulleys/MS20220-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.