

**Description**

MS20220A2 Groove Pulley

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20220A2
Minimum Qty (MOQ):	1
NSN:	3020-00-528-7993
ECCN:	EAR99
National Motor Freight:	127320, Pulleys / Sheaves,noi



\* See page 2 for technical characteristics

P/N MS20220A2 Specifications

Groove Depth:	0.250 Inches Nominal
Groove Width:	0.255 Inches Minimum And 0.275 Inches Maximum
Outside Diameter:	3.005 Inches Nominal
Overall Length:	0.620 Inches Minimum And 0.625 Inches Maximum
Bore Diameter:	0.313 Inches Nominal
Bore Length:	0.620 Inches Minimum And 0.625 Inches Maximum
End Item Identification:	Aircraft, F-16
Groove Radius:	0.094 Inches Minimum And 0.097 Inches Maximum
Material And Location:	Aluminum Alloy, Qq-a-268, T4-canceled Overall Or Aluminum Alloy, Qq-a-355, T4-canceled Overall
Face Width:	0.422 Inches Nominal
Design Form:	Plain
Bore Type:	Straight
Bearings:	Included
Groove Quantity:	1
Counterbore Feature:	Not Included
Bearing Quantity:	2
Keying Facility:	Not Included
Split Hub Feature:	Not Included
Lightening Hole:	Not Included
Integral Cooling Vane:	Not Included
Groove Shape:	U
Bore Feature:	Included
Bearing Type:	Ball
Hub End Outside Diameter And Location:	0.485 Inches Minimum Both Ends And 0.545 Inches Maximum Both Ends
Distance From Outside Flange/rim To Hub End And Location:	0.099 Inches Minimum Both Ends And 0.102 Inches Maximum Both Ends
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Surface Treatment:	Anodize
Style Designator:	Plain
Surface Treatment:	Anodized

## How to Order

Order this groove pulley from our inventory online by visiting <https://military-fasteners.com/pulleys/groove+pulleys/MS20220A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.