

Description

Thread Size: 1/8", Nut Height: 1/8", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | MS20364D832A |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5310-00-263-2866 |
| Schedule B: | 7616.10.1000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |



* See page 2 for technical characteristics

P/N MS20364D832A Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Nut Style: | Hexagon |
| Nut Height: | 0.172 Inches Nominal |
| Width Across Flats: | 0.344 Inches Nominal |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Bearing Surface Type: | Flat |
| Material: | Aluminum Alloy Nut |
| Surface Treatment: | Anodize Nut |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS20364D832A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.