

# P/N MS20365-440A

## **Description**

Thread Size: 1/8", Nut Height: 1/8", Head Width: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

## MS21044N04

SKU / Model: MS20365440A

Minimum Qty (MOQ): 50

NSN: 5310-00-088-0551

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS20365-440A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Counterbore Diameter:	0.116 Inches Minimum Nut And 0.156 Inches Maximum Nut
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.133 Inches Minimum And 0.157 Inches Maximum
End Item Identification:	Tactical Data System, An/uya-4(v), Aircraft, ( Ac-130h, Mc-130h, Ec-
Width Across Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Nut
Surface Treatment:	Cadmium Nut
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut

## **How to Order**

Order this self-locking hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS20365-440A">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS20365-440A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.