

Description

MS20392-13P17 Straight Headed Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | MS2039213P17 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5315-01-308-6130 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |



* See page 2 for technical characteristics

P/N MS20392-13P17 Specifications

| | |
|--|--|
| Head Style: | Pan No. 2 (r1 Not Required In Item Description) |
| Chamfer Length: | 0.046 Inches Nominal |
| Diameter: | 0.153 Inches Minimum And 0.155 Inches Maximum |
| Under Head Length: | 0.647 Inches Minimum And 0.667 Inches Maximum |
| Hole Arrangement Style: | One End Drilled |
| First Hole Diameter: | 0.060 Inches Minimum And 0.080 Inches Maximum |
| Distance From Centerline Of Hole To End Of Pin: | 0.091 Inches Nominal |
| Pin Chamfer Angle: | 15.0 Degrees Nominal |
| Shear Strength: | 4780 Double Pound |
| Pin Head Diameter: | 0.281 Inches Nominal |
| Height: | 0.046 Inches Nominal |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Astm A380 Assn Std Single Treatment Response Overall |
| Style Designator: | Straight |

How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-13P17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.