

**Description**

MS20392-13R19 Straight Headed Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2039213R19
Minimum Qty (MOQ):	2
NSN:	5315-01-446-6241
ECCN:	EAR99
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc



NO IMAGE  
AVAILABLE

## P/N MS20392-13R19 Specifications

<b>Head Style:</b>	Pan No. 2 (r1 Not Required In Item Description)
<b>Chamfer Length:</b>	0.046 Inches Nominal
<b>Diameter:</b>	0.153 Inches Minimum And 0.155 Inches Maximum
<b>Under Head Length:</b>	0.730 Inches Minimum And 0.740 Inches Maximum
<b>Hole Arrangement Style:</b>	One End Drilled
<b>First Hole Diameter:</b>	0.060 Inches Minimum And 0.080 Inches Maximum
<b>Distance From Centerline Of Hole To End Of Pin:</b>	0.090 Inches Nominal
<b>Pin Chamfer Angle:</b>	15.0 Degrees Nominal
<b>Shear Strength:</b>	4360 Double Pound
<b>Pin Head Diameter:</b>	0.281 Inches Nominal
<b>Height:</b>	0.046 Inches Nominal
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Chromium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-c-320, Cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Straight

## How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-13R19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.