

Description

MS20392-13R19 Straight Headed Pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2039213R19
Minimum Qty (MOQ):	2
NSN:	5315-01-446-6241
ECCN:	EAR99
National Motor Freight:	105840, Nails / Spikes I / S Noi Plain Etc



* See page 2 for technical characteristics

P/N MS20392-13R19 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.046 Inches Nominal
Diameter:	0.153 Inches Minimum And 0.155 Inches Maximum
Under Head Length:	0.730 Inches Minimum And 0.740 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.060 Inches Minimum And 0.080 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.090 Inches Nominal
Pin Chamfer Angle:	15.0 Degrees Nominal
Shear Strength:	4360 Double Pound
Pin Head Diameter:	0.281 Inches Nominal
Height:	0.046 Inches Nominal
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Chromium Overall
Surface Treatment Document And Classification:	Qq-c-320, Cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-13R19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.