

Description

length: 11/32", diameter: 1/8", straight drilled shank, cadmium plated steel alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS203921C11](#)

SKU / Model:	MS203921C11
Minimum Qty (MOQ):	25
NSN:	5315-00-811-9102
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS20392-1C11 Specifications

Head Style:	Pan No. 2 (r1 Not Required In Item Description)
Chamfer Length:	0.062 Inches Maximum
Diameter:	0.125 Inches Nominal
Under Head Length:	0.460 Inches Minimum And 0.480 Inches Maximum
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.060 Inches Minimum And 0.080 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.091 Inches Nominal
Hardness Rating:	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Pin Chamfer Angle:	14.5 Degrees Minimum And 15.5 Degrees Maximum
Shear Strength:	1840 Double Pound
Pin Head Diameter:	0.234 Inches Minimum And 0.266 Inches Maximum
Special Features:	Shank End May Have Either A Chamfer Or Radius At The Option Of The Vendor
Height:	0.030 Inches Minimum And 0.062 Inches Maximum
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Straight

How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-1C11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.