

**Description**

length: 29/32", diameter: 1/8", straight drilled shank, cadmium plated steel alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS203921C29
Minimum Qty (MOQ):	50
NSN:	5315-00-080-1943
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



## P/N MS20392-1C29 Specifications

<b>Head Style:</b>	Pan No. 2 (r1 Not Required In Item Description)
<b>Chamfer Length:</b>	0.062 Inches Maximum
<b>Diameter:</b>	0.122 Inches Minimum And 0.124 Inches Maximum
<b>Under Head Length:</b>	1.022 Inches Minimum And 1.042 Inches Maximum
<b>Hole Arrangement Style:</b>	One End Drilled
<b>First Hole Diameter:</b>	0.060 Inches Minimum And 0.080 Inches Maximum
<b>Distance From Centerline Of Hole To End Of Pin:</b>	0.091 Inches Nominal
<b>Hardness Rating:</b>	26.5 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Pin Chamfer Angle:</b>	14.5 Degrees Minimum And 15.5 Degrees Maximum
<b>Pin Head Diameter:</b>	0.234 Inches Minimum And 0.266 Inches Maximum
<b>Special Features:</b>	Pin Chamfer End May Be 0.031 In. Nom Radius,in Lieu Of Chamfer
<b>Height:</b>	0.030 Inches Minimum And 0.062 Inches Maximum
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall
<b>Material Document And Classification:</b>	Ams 6300 Assn Std 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Straight

## How to Order

Order this straight headed pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headed+pins/MS20392-1C29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.